

View Online at <https://aerobasegroup.com/nsn/5305-01-206-7260>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.616 inches and 0.666 inches

Fastener Length:

Between 0.814 inches and 0.844 inches

Head Style:

Oval countersunk

Head Diameter:

Between 0.2966 inches and 0.3016 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Unthreaded Hole Diameter:

0.070 inches first hole and 0.075 inches first hole

Internal Drive Style:

High-torque

Thread Diameter:

0.190 inches

Grip Length:

Between 0.178 inches and 0.198 inches

Thready Qty Per Inch (tpi):

32

Countersink Angle:

101.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.693 inches first hole and 0.733 inches first hole

Special Features:

Cetyl alcohol application per mil-I-87132, type 2, class 3

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Aluminum and chromate

Surface Treatment Specification:

Mil-c-83488, type 2 class 3 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.