

View Online at <https://aerobasegroup.com/nsn/5305-01-206-8399>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.330 inches

Fastener Length:

Between 0.747 inches and 0.750 inches

Head Style:

Hexagon

Head Height:

Between 0.080 inches and 0.093 inches

Width Between Flats:

Between 0.243 inches and 0.251 inches

First Diameter From Head:

Between 0.096 inches and 0.100 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.420 inches

Internal Drive Style:

Tri-wing recess

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response

Surface Treatment:

Cadmium head and chromate head

Surface Treatment Specification:

Qq-p-416, type 2 class 2 federal specification single treatment response fastener

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.