NSN 5305-01-206-9207

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-206-9207 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.400 inches **Fastener Length:** 1.150 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **First Diameter From Head:** Between 0.091 inches and 0.097 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.750 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303 plus x or steel comp 303se or steel comp 303cu or steel comp 303ma or steel comp 304 or steel comp 304l or steel comp 384 **Surface Treatment: Passivate Surface Treatment Specification:** Astm a380 assn standard single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-206-9207

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0