## NSN 5305-01-207-5926

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-207-5926 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.844 inches and 0.875 inches **Fastener Length:** Between 0.844 inches and 0.875 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.1900 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Stainless steel **Screw Material Specification:** Ams5737 assn standard single material response **Screw Surface Treatment:** Passivate and chromate **Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response and qq-p-416 tyii cl 2 federal specification 2nd treatment response Color: Black **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1100 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## **NSN 5305-01-207-5926** Machine Screw - Page 2 of 2



Fiig:

A500d0