## NSN 5305-01-207-7515

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-207-7515

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.158 inches and 0.250 inches
Fastener Length:
Between 0.220 inches and 0.250 inches
Head Style:
Pan
Head Diameter:
Between 0.357 inches and 0.373 inches
Head Height:
Between 0.122 inches and 0.133 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 36.0 rockwell c and 40.0 rockwell c
Screw Material:
Steel comp 4140 or steel comp e4340 or steel comp 8740
Head Surface Treatment:
Paint
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416, ty2, cl3 federal specification single treatment response
Special Features:
Furnished with boot type nylon washer, head and washer color black per federal standard 595 no. S01bk
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No

## **NSN 5305-01-207-7515**Machine Screw - Page 2 of 2



Fiig:

A500d0