NSN 5305-01-207-7550

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-207-7550 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.381 inches and 0.431 inches **Fastener Length:** Between 0.579 inches and 0.609 inches **Head Style:** Fillister countersunk **Head Diameter:** Between 0.2966 inches and 0.3016 inches **Head Height:** 0.013 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** High-torque **End Application:** Aircraft, hornet f/a-18 (e/f); aircraft, eagle f-15; aircraft, harrier av-8b **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.178 inches and 0.198 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** 101.0 degrees Material: Nickel alloy 718 **Material Specification:** 23-118, inco 718 fscm 76301 mfr ref single material response **Surface Treatment:** Aluminum and chromate **Surface Treatment Specification:** Mil-c-83488, type 2 class 3 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-207-7550

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.