NSN 5305-01-207-8613

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-207-8613 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.323 inches **Fastener Length:** Between 1.246 inches and 1.261 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.338 inches and 0.381 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Internal Drive Style:** Tri-wing recess **Thread Diameter:** 0.1900 inches **Grip Length:** Between 0.928 inches and 0.948 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unjf **Specification Data:** 80205-nas4503 professional/industrial association standard Shelf Life:

N/a
Unit Of Measure:
-Demilitarization:

NSN 5305-01-207-8613

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0