NSN 5305-01-208-0281

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-208-0281 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.313 inches and 0.363 inches **Fastener Length:** Between 1.073 inches and 1.103 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.339 inches and 0.381 inches **Shoulder Diameter:** 0.2046 inches and 0.2051 inches first shoulder **Shoulder Length:** 0.667 inches and 0.687 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder Material: Titanium alloy **Material Specification:** Ams4928jgaams4967, comp 6al-4v assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1790 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-208-0281

Shoulder Screw - Page 2 of 2



Fiig:

A003b0