NSN 5305-01-208-2887

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-208-2887 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.809 inches and 0.891 inches **Fastener Length:** Between 0.859 inches and 0.891 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **Locking Feature:** Patch threads **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard single material response or ams5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1742 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-208-2887

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0