NSN 5305-01-208-3848

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-208-3848 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.560 inches **Fastener Length:** 2.560 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.309 inches and 0.311 inches **Head Height:** 1.000 inches **Hole Diameter:** Between 0.125 inches and 0.129 inches First Diameter From Head: Between 0.180 inches and 0.190 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.000 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches **Hole Quantity:** 1 **Hole Type:** Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 115000 pounds per square inch **Hole Configuration Style:** Round **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303se **Material Specification:** Astm a582 assn standard single material response

Passivate

Surface Treatment:

NSN 5305-01-208-3848

Externally Relieved Body Screw - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A003b0