## NSN 5305-01-208-5214

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-208-5214

Thread Class:						
3a						
Thread Direction:						
Right-hand						
Thread Length:						
Between 0.220 inches and 0.312 inches						
Fastener Length:						
Between 0.282 inches and 0.312 inches						
Head Style:						
Flat chamfer						
Head Diameter:						
Between 0.218 inches and 0.226 inches						
Head Height:						
Between 0.134 inches and 0.138 inches						
Locking Feature:						
Strip threads						
Internal Drive Style:						
Hexagon						
Thread Diameter:						
0.138 inches						
Width Across Flats:						
Between 0.1094 inches and 0.1111 inches						
Thready Qty Per Inch (tpi):						
32						
Min. Tensile Strength (psi):						
80000 pounds per square inch						
Hardness Rating:						
80.0 rockwell b						
Material:						
Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7 fastener						
Material Specification:						
Astm a493 assn standard all material responses fastener						
Surface Treatment:						
Passivate fastener						
Surface Treatment Specification:						
Qq-p-35 federal specification single treatment response fastener						
Thread Series Designator:						
Unrc						
Specification Data:						
80205-nas1352 professional/industrial association standard						
Shelf Life:						

N/a

## NSN 5305-01-208-5214

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0