NSN 5305-01-208-5236

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-208-5236

| Thread Class: | |
|--|--|
| 2a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| 3.250 inches | |
| Fastener Length: | |
| 5.250 inches | |
| Head Style: | |
| Pan no. 2 | |
| Head Diameter: | |
| 2.750 inches | |
| Head Height: | |
| 1.880 inches | |
| Hole Diameter: | |
| 0.070 inches | |
| Internal Drive Style: | |
| Hexagon | |
| Thread Diameter: | |
| 1.875 inches | |
| Width Across Flats: | |
| 1.502 inches | |
| Hole Quantity: | |
| 6 | |
| Hole Type: | |
| Drilled | |
| Thready Qty Per Inch (tpi): | |
| 12 | |
| Hole Configuration Style: | |
| Round internal hexagon | |
| Criticality Code Justification: | |
| Zzzy | |
| Material: | |
| Stainless steel | |
| Material Specification: | |
| Astm a193, grade b8r assn standard single material response | |
| Surface Treatment: | |
| Chromium | |
| Surface Treatment Specification: | |
| Mil-c-23422 military specification single treatment response | |
| Thread Series Designator: | |

Un

NSN 5305-01-208-5236

Socket Head Cap Screw - Page 2 of 2



Reference Number Differentiating Characteristics:

| Material will be in accordance with ships parts control center act | ctivity hx quality control, manufacturing and testing specifications |
|--|--|
|--|--|

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-23422 spec.