NSN 5305-01-208-6723

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-208-6723

Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.372 inches and 0.422 inches **Fastener Length:** Between 1.320 inches and 1.350 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.3898 inches and 0.3948 inches **Shoulder Diameter:** 0.2646 inches and 0.2651 inches first shoulder **Shoulder Length:** 0.861 inches and 0.885 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Hex hole on threaded end with 0.0947 min and 0.0967 maximum in. Dia, 0.115 min and 0.135 maximum in. Deep Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

NSN 5305-01-208-6723

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0