## NSN 5305-01-208-7566

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-208-7566 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.111 inches **Fastener Length:** Between 2.210 inches and 2.250 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.600 inches and 0.656 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: 0.188 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 80000 pounds per square inch **Hardness Rating:** 80.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 84.0 degrees **Product Name:** Navy special project Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 4 type

N/a

Shelf Life:

## NSN 5305-01-208-7566

Socket Head Cap Screw - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0