

View Online at <https://aerobasegroup.com/nsn/5305-01-208-7964>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.828 inches and 1.969 inches

Fastener Length:

Between 1.922 inches and 1.969 inches

Head Style:

Hexagon

Head Height:

Between 0.080 inches and 0.095 inches

Width Between Flats:

Between 0.241 inches and 0.250 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

Screw Material:

Steel comp 8630 or steel comp 4037

Screw Material Specification:

Mil-s-6050 military specification 1st material response or ams6300 assn standard 2nd material response

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416, type 2 class 2 federal specification single treatment response

Thread Series Designator:

Unc

Specification Data:

80205-nas1096 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.