NSN 5305-01-209-1053

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-209-1053

| Through Classes |
|---|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.485 inches and 0.577 inches |
| Fastener Length: |
| Between 0.547 inches and 0.577 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.256 inches and 0.270 inches |
| Head Height: |
| Between 0.087 inches and 0.097 inches |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.138 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| Between 24.0 rockwell c and 35.0 rockwell c |
| Screw Material: |
| Iron alloy 660 |
| Screw Material Specification: |
| Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single |
| material response |
| Screw Surface Treatment: |
| Passivate |
| Screw Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjc |
| Specification Data: |
| 80205-nas1216 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5305-01-209-1053

Machine Screw - Page 2 of 2



Fiig:

A500d0