NSN 5305-01-209-1779

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-209-1779

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.400 inches |
| Fastener Length: |
| 0.878 inches |
| Head Style: |
| Flat fillister |
| Head Diameter: |
| Between 0.200 inches and 0.210 inches |
| Head Height: |
| Between 0.255 inches and 0.260 inches |
| Hole Diameter: |
| 0.112 inches |
| Internal Drive Style: |
| W/o internal drive |
| Thread Diameter: |
| 0.112 inches |
| Hole Quantity: |
| 1 |
| Thready Qty Per Inch (tpi): |
| 40 |
| Screw Material: |
| Steel comp 303 |
| Screw Material Specification: |
| Astm a582 assn standard single material response |
| Screw Surface Treatment: |
| Passivate |
| Screw Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Head Hole Configuration Style: |
| Round longitudinal hole |
| Special Features: |
| Hole in head threaded 0.112-40-unc x 0.220 in. Dp |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| Onit Of Wicasule. |

NSN 5305-01-209-1779

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0