NSN 5305-01-209-4718

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-209-4718 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.444 inches and 0.494 inches **Fastener Length:** Between 1.016 inches and 1.046 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.578 inches and 0.634 inches **Shoulder Diameter:** 0.3427 inches and 0.3432 inches first shoulder **Shoulder Length:** 0.432 inches and 0.452 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder Material: Titanium alloy **Material Specification:** Ams4928 assn standard single material response or ams4967, comp 6al-4v assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1790 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-209-4718

Shoulder Screw - Page 2 of 2



Fiig:

A003b0