

View Online at <https://aerobasegroup.com/nsn/5305-01-209-7109>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.303 inches and 0.313 inches

**Fastener Length:**

Between 0.860 inches and 0.890 inches

**Head Style:**

Knurled no. 1

**Head Diameter:**

Between 0.495 inches and 0.505 inches

**Head Height:**

Between 0.547 inches and 0.577 inches

**Point Length:**

0.313 inches

**Point Diameter:**

Between 0.155 inches and 0.159 inches

**First Diameter From Head:**

Between 0.170 inches and 0.180 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.254 inches

**Point Style:**

Cone

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

20

**Externally Relieved Body Diameter Quantity:**

1

**Point Chamfer Angle:**

90.0 degrees

**Material:**

Steel comp 303 or steel comp 303 plus x or steel comp 303ma or steel comp 303se or steel comp 416 or steel comp 416 plus x or steel comp 416se or steel comp 430f or steel comp 430fse or steel comp 420f or steel comp 420fse or steel comp 440f

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35, type 4 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0