Externally Relieved Body Screw - Page 1 of 2



plus x or steel

View Online at https://aerobasegroup.com/nsn/5305-01-209-7109

Thread C	lass:
2a	
Thread D	irection:
Right-han	d
Thread L	ength:
Between	0.303 inches and 0.313 inches
Fastener	Length:
Between	0.860 inches and 0.890 inches
Head Sty	le:
Knurled n	o. 1
Head Dia	meter:
Between	0.495 inches and 0.505 inches
Head Hei	ght:
Between	0.547 inches and 0.577 inches
Point Ler	igth:
0.313 incl	nes
Point Dia	meter:
Between	0.155 inches and 0.159 inches
First Diar	neter From Head:
Between	0.170 inches and 0.180 inches
Distance	From Largest Bearing Surface Of Head To End Of First Diameter:
0.254 incl	nes
Point Sty	le:
Cone	
Internal D	Drive Style:
Slot	
Thread D	iameter:
0.250 incl	nes
Thready	Qty Per Inch (tpi):
20	
Externall	y Relieved Body Diameter Quantity:
1	
Point Cha	amfer Angle:
90.0 degr	ees
Material:	
Steel com	p 303 or steel comp 303 plus x or steel comp 303ma or steel comp 303se or steel comp 416 or steel comp 416
	se or steel comp 430f or steel comp 430fse or steel comp 420f or steel comp 420fse or steel comp 440f
	reatment:
Passivate	
Surface 1	reatment Specification:
	type 4 federal specification single treatment response
	avies Designatory

Thread Series Designator:

Unc

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0