NSN 5305-01-209-7178

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-209-7178

Thread Class:
3a
Thread Direction:
Right-hand
•
Thread Length: Between 0.358 inches and 0.438 inches
Fastener Length: Between 0.408 inches and 0.438 inches
Head Style:
Flat chamfer Lead Diameter
Head Diameter:
Between 0.176 inches and 0.183 inches
Head Height:
Between 0.108 inches and 0.112 inches
Hole Diameter:
Between 0.033 inches and 0.039 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.112 inches
Width Across Flats:
Between 0.094 inches and 0.095 inches
Hole Quantity:
2
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Hole Configuration Style:
Round internal hexagon
Material:
Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp xm-7 or steel comp 384
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unrc

NSN 5305-01-209-7178

Socket Head Cap Screw - Page 2 of 2



Specification D	ata:
-----------------	------

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0