NSN 5305-01-209-7888

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-209-7888

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.608 inches and 0.749 inches
Fastener Length:
Between 0.734 inches and 0.781 inches
Head Style:
Hexagon
Head Height:
Between 0.080 inches and 0.093 inches
Width Between Flats:
Between 0.243 inches and 0.251 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 36.0 rockwell c and 40.0 rockwell c
Screw Material:
Iron alloy 660
Screw Material Specification:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjc
Specification Data:
80205-nas1802 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-01-209-7888

Machine Screw - Page 2 of 2



Fiig:

A500d0