## NSN 5305-01-209-7889

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-209-7889

Thread Class:							
3a							
Thread Direction:							
Right-hand							
Thread Length:							
Between 0.346 inches and 0.386 inches							
Fastener Length:							
Between 0.428 inches and 0.448 inches							
Head Style:							
Double hexagon w/ hole							
Head Height:							
Between 0.220 inches and 0.240 inches							
Width Between Flats:							
0.2188 inches							
Extended Washer Diameter:							
Between 0.302 inches and 0.322 inches							
Extended Washer Thickness:							
Between 0.030 inches and 0.050 inches							
Hole Diameter:							
0.047 inches							
End Application:							
Spec item							
Thread Diameter:							
0.164 inches							
Hole Quantity:							
4							
Thready Qty Per Inch (tpi):							
36							
Min. Tensile Strength (psi):							
130000 pounds per square inch							
Hardness Rating:							
Between 24.0 rockwell c and 35.0 rockwell c							
Screw Material:							
Iron alloy 660							
Screw Material Specification:							
Ams5731 assn standard single material response							
Head Hole Configuration Style:							
Double hexagon longitudinal hole							
Thread Series Designator:							
Unjf							
Shelf Life:							
N/a							

## NSN 5305-01-209-7889

Machine Screw - Page 2 of 2



	• •						
ın	1+	Of	ΝЛ	ດລ	CI.	ırı	ο.

--

Demilitarization:

No

Fiig:

A500d0