NSN 5305-01-209-7936

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-209-7936

Thread Class:
3a
Thread Direction:
Right-hand Thread Longth:
Thread Length:
Between 0.400 inches and 0.450 inches
Fastener Length:
Between 0.848 inches and 0.878 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.464 inches and 0.506 inches
Shoulder Diameter:
0.2646 inches and 0.2651 inches first shoulder
Shoulder Length:
0.329 inches and 0.349 inches first shoulder
Internal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Shoulder Shape:
Round first shoulder
Material:
Titanium alloy
Material Specification:
Ams4928 assn standard single material response or ams4967, comp 6al-4v assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1790 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
<u></u>
Demilitarization:
No

NSN 5305-01-209-7936

Shoulder Screw - Page 2 of 2



Fiig:

A003b0