

View Online at <https://aerobasegroup.com/nsn/5305-01-209-7938>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.400 inches and 0.450 inches

**Fastener Length:**

Between 1.535 inches and 1.565 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.464 inches and 0.506 inches

**Shoulder Diameter:**

0.2646 inches and 0.2651 inches first shoulder

**Shoulder Length:**

1.016 inches and 1.036 inches first shoulder

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Shoulder Shape:**

Round first shoulder

**Material:**

Titanium alloy

**Material Specification:**

Ams4928 assn standard single material response or ams4967, comp 6al-4v assn standard single material response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1790 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0