## NSN 5305-01-209-7946

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-209-7946 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.380 inches and 0.447 inches **Fastener Length:** Between 1.078 inches and 1.125 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.377 inches and 0.381 inches **Head Height:** Between 0.032 inches and 0.034 inches **Shoulder Diameter:** 0.2177 inches and 0.2182 inches first shoulder **Shoulder Length:** 0.644 inches and 0.666 inches first shoulder **Internal Drive Style:** High-torque Thread Diameter: 0.190 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** 100.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Furnished with one o-ring Material: Titanium alloy **Material Specification:** Ams 4967, comp 6al-4v assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5305-01-209-7946

Shoulder Screw - Page 2 of 2



Fiig:

A003b0