NSN 5305-01-209-7949



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-209-7949 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.553 inches and 0.603 inches **Fastener Length:** Between 1.251 inches and 1.281 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.717 inches and 0.760 inches **Shoulder Diameter:** 0.3896 inches and 0.3901 inches first shoulder **Shoulder Length:** 0.525 inches and 0.545 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Shoulder Shape:

Round first shoulder

Material:

Titanium alloy

Material Specification:

Ams4928 6al-4v assn standard single material response or ams4967 6al-4v assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1790 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5305-01-209-7949

Shoulder Screw - Page 2 of 2



Fiig:

A003b0