NSN 5305-01-209-7952

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-209-7952

Threa	d Class:
3a	
Threa	d Direction:
Right-	hand
Threa	d Length:
Betwe	en 0.338 inches and 0.388 inches
Faste	ner Length:
Betwe	en 1.536 inches and 1.566 inches
Head	Style:
Flat co	puntersunk
Head	Diameter:
Betwe	en 0.339 inches and 0.381 inches
Grip [Diameter:
Betwe	en 0.1890 inches and 0.1895 inches
Intern	al Drive Style:
High-t	orque
Threa	d Diameter:
0.190	inches
Grip L	_ength:
Betwe	en 1.178 inches and 1.198 inches
Threa	dy Qty Per Inch (tpi):
32	
Min. T	ensile Strength (psi):
16000	0 pounds per square inch
Hardn	ness Rating:
2.0 ro	ckwell c and 35.0 rockwell c
Count	tersink Angle:
Betwe	en 99.0 degrees and 101.0 degrees
Surfa	ce Finish:
32.0 n	nicroinches threads
Mater	ial:
Iron al	lloy 660
Mater	ial Specification:
Ams 5	i731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single
materi	ial response
Surfa	ce Treatment:
Passiv	vate
Surfa	ce Treatment Specification:
Qq-p-	35 federal specification single treatment response
Threa	d Series Designator:
Unjf	
Speci	fication Data:
80205	i-nas1580 professional/industrial association standard

NSN 5305-01-209-7952

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

