

View Online at <https://aerobasegroup.com/nsn/5305-01-209-9325>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.208 inches and 0.258 inches

**Fastener Length:**

Between 0.593 inches and 0.623 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.194 inches and 0.225 inches

**Internal Drive Style:**

Torque set

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

Between 36.0 rockwell c and 40.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Screw Material:**

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416, ty2, cl2 federal specification single treatment response

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0