NSN 5305-01-209-9361

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-209-9361 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.444 inches and 0.494 inches **Fastener Length:** Between 1.204 inches and 1.234 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.578 inches and 0.634 inches **Shoulder Diameter:** 0.3271 inches and 0.3276 inches first shoulder **Shoulder Length:** 0.614 inches and 0.634 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder Material: Titanium alloy **Material Specification:** Ams4928 assn standard single material response or ams4967, comp 6al-4v assn standard single material response **Thread Series Designator:** Unjf

Specification Data:

80205-nas1790 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5305-01-209-9361

Shoulder Screw - Page 2 of 2



Fiig:

A003b0