NSN 5305-01-209-9372

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-209-9372

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.372 inches and 0.422 inches
Fastener Length:
Between 1.632 inches and 1.662 inches
Head Style:
Fillister countersunk
Head Diameter:
Between 0.3898 inches and 0.3948 inches
Head Height:
0.015 inches
Shoulder Diameter:
0.2646 inches and 0.2651 inches first shoulder
Shoulder Length:
1.183 inches and 1.211 inches first shoulder
nternal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Гhready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
125000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Shoulder Shape:
Round first shoulder
Special Features:
Hex hole in threaded end 0.095 min and 0.097 max
Material:
Steel comp xm-13
Material Specification:
Ams5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qa-p-35 federal specification single treatment response

Unjf

Thread Series Designator:

NSN 5305-01-209-9372

Shoulder Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0