NSN 5305-01-209-9380

Panel Screw Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-209-9380

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.297 inches and 0.327 inches
Fastener Length:
0.438 inches
Head Style:
Knurled no. 3
Head Diameter:
Between 0.285 inches and 0.315 inches
Head Height:
0.750 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
1600 pounds per square inch
Special Features:
Knurled portion of fastner internally threaded d1a. 0.250, 28 threads per inch unf, 3b also contains screw hold-out spring
Material:
Steel comp 302 or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or
steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel
comp 347 or steel comp 303ma or steel comp 303 plus x
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0