NSN 5305-01-210-0776

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-210-0776 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.297 inches and 0.391 inches **Fastener Length:** Between 0.359 inches and 0.391 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.1094 inches and 0.1111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 74.0 rockwell b Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 1 class 2 federal specification single treatment response **Thread Series Designator:** Unrc **Specification Data:** 80205-nas1352 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-210-0776

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0