
Socket Head Cap Screw - Page 1 of 2





Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.297 inches and 0.391 inches

Fastener Length:

Between 0.359 inches and 0.391 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.218 inches and 0.226 inches

Head Height:

Between 0.134 inches and 0.138 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.138 inches

Width Across Flats:

Between 0.1094 inches and 0.1111 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

74.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

Material:

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1 class 2 federal specification single treatment response

Thread Series Designator:

Unrc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-01-210-0776

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

