NSN 5305-01-210-7668

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-210-7668 Thread Length: 0.420 inches **Fastener Length:** 0.970 inches **Head Style:** Hexagon **Head Height:** Between 0.134 inches and 0.138 inches Width Between Flats: Between 0.218 inches and 0.226 inches **Locking Feature:** Undercut **Point Length:** 0.170 inches **Point Diameter:** Between 0.920 inches and 0.925 inches First Diameter From Head: Between 0.905 inches and 0.915 inches **Second Diameter From Head:** Between 0.136 inches and 0.137 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.160 inches and 0.170 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.220 inches and 0.230 inches **Internal Drive Style:** Hexagon Width Across Flats: Between 0.109 inches and 0.111 inches **Askewed Head Angle:** 120.0 degrees **Externally Relieved Body Diameter Quantity: Point Chamfer Angle:** 45.0 degrees Material: Steel comp 630 Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-210-7668

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0