

View Online at https://aerobasegroup.com/nsn/5305-01-210-7668

Thread Length	n:
0.420 inches	
Fastener Leng	jth:
0.970 inches	
Head Style:	
Hexagon	
Head Height:	
Between 0.134	inches and 0.138 inches
Width Betwee	n Flats:
Between 0.218	inches and 0.226 inches
Locking Featu	ire:
Undercut	
Point Length:	
0.170 inches	
Point Diamete	r:
Between 0.920	inches and 0.925 inches
First Diameter	<sup>r</sup> From Head:
Between 0.905	inches and 0.915 inches
Second Diame	eter From Head:
Between 0.136	inches and 0.137 inches
Distance From	n Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.160	inches and 0.170 inches
Distance From	n Largest Bearing Surface Of Head To End Of Second Diameter:
Between 0.220	inches and 0.230 inches
Internal Drive	Style:
Hexagon	
Width Across	Flats:
Between 0.109	inches and 0.111 inches
Askewed Head	d Angle:
120.0 degrees	
Externally Rel	ieved Body Diameter Quantity:
3	
Point Chamfer	r Angle:
45.0 degrees	
Material:	
Steel comp 630	0
Shelf Life:	
N/a	
Unit Of Measu	ire:
Demilitarizatio	on:
No	

## NSN 5305-01-210-7668

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

