## NSN 5305-01-210-9433

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-210-9433 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.865 inches and 0.885 inches **Fastener Length:** Between 1.990 inches and 2.010 inches **Head Style:** Flat chamfer **Head Diameter:** 0.562 inches **Head Height:** Between 0.368 inches and 0.375 inches **Shoulder Diameter:** 0.365 inches first shoulder and 0.375 inches first shoulder **Shoulder Length:** 0.708 inches first shoulder and 0.718 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.3125 inches and 0.3155 inches Thready Qty Per Inch (tpi): 18 **Shoulder Shape:** Round first shoulder **Special Features:** Undercut 0.286 in. Min dia, 0.306 in maximum dia; 0.075 in. Min length, 0.080 in. Maximum length **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## **NSN 5305-01-210-9433** Shoulder Screw - Page 2 of 2



Fiig:

A003b0