## NSN 5305-01-210-9436

Shoulder Screw - Page 1 of 2

**Thread Class:** 

3a

28

View Online at https://aerobasegroup.com/nsn/5305-01-210-9436



## **Thread Direction: Right-hand Thread Length:** Between 0.400 inches and 0.450 inches Fastener Length: Between 0.785 inches and 0.815 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.464 inches and 0.506 inches Shoulder Diameter: 0.2802 inches and 0.2807 inches first shoulder Shoulder Length: 0.270 inches and 0.290 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder Material: Titanium alloy **Material Specification:** Ams4928 assn standard single material response or ams4967, comp 6al-4v assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1790 professional/industrial association standard Shelf Life: N/a Unit Of Measure: **Demilitarization:**

No

---

## **NSN 5305-01-210-9436** Shoulder Screw - Page 2 of 2

Fiig: A003b0

