NSN 5305-01-211-1470

Shoulder Screw - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5305-01-211-1470

3a
Thread Direction:
Right-hand
Thread Length:
0.617 inches
Fastener Length:
0.820 inches
Head Style:
Flat chamfer
Head Diameter:
0.562 inches
Head Height:
Between 0.244 inches and 0.250 inches
Shoulder Diameter:
0.371 inches and 0.373 inches first shoulder
Shoulder Length:
0.125 inches first shoulder
Internal Drive Style:
Hexagon
Thread Diameter:
0.312 inches
Width Across Flats:
Between 0.187 inches and 0.189 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
150000 pounds per square inch
Hardness Rating:
33.0 rockwell c and 39.0 rockwell c
Minimum Yield Strength:
130000 pounds per square inch
Shoulder Shape:
Round first shoulder
Material:
Steel
Material Specification:
Sae j429, gr 8 assn standard single material response
Surface Treatment:
Zinc
Surface Treatment Specification:
Astm b633, type 1, cl fe zn5 assn standard single treatment response

NSN 5305-01-211-1470

Shoulder Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0