
## NSN 5305-01-211-1475

Close Tolerance Screw - Page 1 of 2





Thread Class
Thread Class:
3a Thread Direction:
Right-hand
·
Thread Length: Between 0.444 inches and 0.494 inches
Fastener Length: Between 1.016 inches and 1.046 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.456 inches and 0.508 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Grip Length:
Between 0.552 inches and 0.572 inches
Thready Qty Per Inch (tpi):
28
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Special Features:
With cetyl alcohol per mil-l-87132, ty1, grb as a lubricant
Material:
Steel comp xm-13
Material Specification:
Ams5629 assn standard single material response
Surface Treatment:
Aluminum and chromate
Surface Treatment Specification:
Mil-c-83488, ty2, cl3 military specification single treatment response
Thread Series Designator:
Unif
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No

## NSN 5305-01-211-1475

Close Tolerance Screw - Page 2 of 2

**Fiig:** A003b0

Mil-std (military Standard):

Mil-c-83488 spec.

