

View Online at <https://aerobasegroup.com/nsn/5305-01-211-4348>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.444 inches and 0.494 inches

**Fastener Length:**

Between 1.329 inches and 1.359 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.578 inches and 0.634 inches

**Shoulder Diameter:**

0.3427 inches and 0.3432 inches first shoulder

**Shoulder Length:**

0.745 inches and 0.765 inches first shoulder

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.312 inches

**Thread Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Shoulder Shape:**

Round first shoulder

**Material:**

Titanium alloy

**Material Specification:**

Ams4928 assn standard single material response or ams4967, comp 6al-4v assn standard single material response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1790 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0