## NSN 5305-01-211-5010

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-211-5010 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.312 inches **Fastener Length:** Between 1.080 inches and 1.110 inches **Head Style:** Hexagon **Head Height:** Between 0.140 inches and 0.160 inches Width Between Flats: Between 0.367 inches and 0.375 inches **Internal Drive Style:** Hexagon **Material Accommodated Thickness:** 0.125 inches **Thread Diameter:** 0.190 inches Width Across Flats: Between 0.1562 inches and 0.1587 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch Hardness Rating: 35.0 rockwell c and 43.0 rockwell c primary washer **Special Features:** Internal threads in sleeve section; 0.250-28 unf-2b Material: Steel comp 302 spring **Material Specification:** Qq-w-423 federal specification single material response spring **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf

Shelf Life:

N/a

## NSN 5305-01-211-5010

Panel Screw Assembly - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5059 spec.