

View Online at <https://aerobasegroup.com/nsn/5305-01-211-5010>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.312 inches

**Fastener Length:**

Between 1.080 inches and 1.110 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.140 inches and 0.160 inches

**Width Between Flats:**

Between 0.367 inches and 0.375 inches

**Internal Drive Style:**

Hexagon

**Material Accommodated Thickness:**

0.125 inches

**Thread Diameter:**

0.190 inches

**Width Across Flats:**

Between 0.1562 inches and 0.1587 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

130000 pounds per square inch

**Hardness Rating:**

35.0 rockwell c and 43.0 rockwell c primary washer

**Special Features:**

Internal threads in sleeve section; 0.250-28 unf-2b

**Material:**

Steel comp 302 spring

**Material Specification:**

Qq-w-423 federal specification single material response spring

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5059 spec.