NSN 5305-01-211-6952

Shoulder Screw - Page 1 of 2

Thread Class:

Thread Direction:

2a



View Online at https://aerobasegroup.com/nsn/5305-01-211-6952

Right-hand
Thread Length:
0.625 inches
Fastener Length:
4.625 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.543 inches and 0.562 inches
Head Height:
Between 0.240 inches and 0.250 inches
Shoulder Diameter:
0.4960 inches and 0.4980 inches first shoulder
Shoulder Length:
4.000 inches first shoulder
Hole Diameter:
Between 0.061 inches and 0.067 inches
Single Shear Strength:
84000 pounds per square inch
Internal Drive Style:
Hexagon
Thread Diameter:
0.375 inches
Width Across Flats:
0.188 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
140000 pounds per square inch
Hardness Rating:
32.0 rockwell c and 43.0 rockwell c
Hole Configuration Style:
Round internal hexagon
Shoulder Shape:
Round first shoulder

NSN 5305-01-211-6952

Shoulder Screw - Page 2 of 2

A003b0



Material:
Steel
Surface Treatment:
Zinc
Surface Treatment Specification:
Qq-z-35, ty2, cl3 federal specification single treatment response
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia: