NSN 5305-01-211-7485

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-211-7485 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.276 inches and 0.338 inches **Fastener Length:** Between 0.448 inches and 0.478 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.2966 inches and 0.3016 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Torque-set ribbed **Thread Diameter:** 0.190 inches **Grip Length:** 0.125 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 95000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 class 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5305-01-211-7485

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0