

View Online at <https://aerobasegroup.com/nsn/5305-01-211-7485>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.276 inches and 0.338 inches

Fastener Length:

Between 0.448 inches and 0.478 inches

Head Style:

Oval countersunk

Head Diameter:

Between 0.2966 inches and 0.3016 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Internal Drive Style:

Torque-set ribbed

Thread Diameter:

0.190 inches

Grip Length:

0.125 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

95000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches threads

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2 class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0