NSN 5305-01-212-2279

Shoulder Screw - Page 1 of 2

3a

24

View Online at https://aerobasegroup.com/nsn/5305-01-212-2279



Thread Class: Thread Direction: Right-hand Thread Length: Between 0.553 inches and 0.603 inches Fastener Length: Between 1.188 inches and 1.218 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.717 inches and 0.760 inches Shoulder Diameter: 0.3896 inches and 0.3901 inches first shoulder Shoulder Length: 0.462 inches and 0.482 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Shoulder Shape: Round first shoulder Material: Titanium alloy **Material Specification:** Ams4928 6al-4v assn standard single material response or ams4967 6al-4v assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1790 professional/industrial association standard Shelf Life: N/a Unit Of Measure: **Demilitarization:**

No

NSN 5305-01-212-2279

Shoulder Screw - Page 2 of 2

Fiig: A003b0

