## NSN 5305-01-212-3447

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-212-3447 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.135 inches and 0.165 inches **Fastener Length:** Between 0.405 inches and 0.435 inches **Head Style:** Hexagon **Head Height:** 0.076 inches Width Between Flats: 0.250 inches **First Diameter From Head:** Between 0.090 inches and 0.094 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.240 inches and 0.300 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 140000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 4037 **Material Specification:** Ams6300 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2class 1 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-01-212-3447

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0