# NSN 5305-01-212-4520

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-212-4520



# **Thread Class:** 3a

Thread Direction:

Right-hand

# Thread Length:

Between 1.482 inches and 1.561 inches

### Fastener Length:

Between 1.546 inches and 1.593 inches

#### Head Style:

Hexagon

Head Height:

Between 0.125 inches and 0.140 inches

### Width Between Flats:

Between 0.367 inches and 0.376 inches

### Internal Drive Style:

Cross recess type 1

#### Thread Diameter:

0.250 inches

### Thready Qty Per Inch (tpi):

28

# Min. Tensile Strength (psi):

160000 pounds per square inch

#### Screw Material:

Steel comp e4340 or steel comp 8740

# Screw Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response

#### **Screw Surface Treatment:**

Cadmium and chromate

# Screw Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

# Thread Series Designator:

Unjf

#### **Specification Data:**

80205-nas1801 professional/industrial association standard

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

# Fiig:

A500d0

# NSN 5305-01-212-4520

Machine Screw - Page 2 of 2

# Mil-std (military Standard):

Mil-s-5000 spec.

