

View Online at <https://aerobasegroup.com/nsn/5305-01-212-5213>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.382 inches and 0.432 inches

Fastener Length:

Between 1.454 inches and 1.484 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.376 inches and 0.385 inches

Grip Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Unthreaded Hole Diameter:

0.070 inches and 0.075 inches first hole

Internal Drive Style:

High-torque

Thread Diameter:

0.190 inches

Grip Length:

Between 1.052 inches and 1.072 inches

Thread Qty Per Inch (tpi):

32

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.333 inches and 1.373 inches first hole

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0